

TAGGTRÅD

PLASTBELAGD

TAGGTRÅD

Produktbeskrivning	Plastbelagd galvaniserad taggtråd Färg mörkgrön, olivgrön och svart
Förpackning	250M
Vikt (kg)	13,7
Diameter tråd	2,10/1,70mm
Diameter tagg	1,80/1,50mm, avstånd 10cm



Dubbeltvinnad HT tråd som är galvad och sedermera plastbelagd genom sintring.
Tråd för tagg är virad kring huvudtrådarna

general characteristics	value		unit of measurement	ref. standards
	riccio	riccio PVC		
maximum single support wire tensile strength	1000-1200*	600-800*	N/mm ²	-
zinc coating type	hot dip	hot dip	-	UNI-EN 10244-2
zinc purity grade (SHG)	~99,995%	~99,995%	-	UNI-EN 1179
zinc adherence	1 (excellent)	1 (excellent)	-	UNI-EN 10244-2
support wire zinc coating thickness	~29	~8,5	µm	-
tips zinc coating thickness	~28	~8,5	µm	-
support wire PVC thickness	-	~0,20	mm	UNI-EN 10218-2
tips PVC thickness	-	~0,15	mm	UNI-EN 10218-2
plastic coating process	-	sintering	-	UNI-EN 10245-2
colour	-	bright alpine green	-	-
ø zinc coated support wire tolerance	±0,05	±0,04	mm	UNI-EN 10218-2
ø plastic coated support wire tolerance	-	±0,10	mm	UNI-EN 10218-2
ø zinc coated barbs tolerance	±0,045	±0,035	mm	UNI-EN 10218-2
ø plastic coated barbs tolerance	-	±0,10	mm	UNI-EN 10218-2

(*) the values refer to the wire before twisting



CAVATORTA

